



December 22, 2021

Re: Shingle Repair

To Whom It May Concern:

The following information confirms the corrective action that is acceptable to Owens Corning regarding repairing damaged shingles. Before making any repairs as described below, it is critical to consider the possibility of damaging shingles when the decision is made to break the seal of an existing roof. **Any damaged or torn shingles must be replaced.** The decision to make corrective repairs to an existing sealed roof is at the discretion of the owner, applicator or specifier.

After repairs have been made, the shingles will need to be manually sealed. For Three-tab Shingles apply two spots of asphalt plastic cement per tab. The spots should be placed one to two inches from each end of the tab and near the bottom, but not so close to the bottom that it is squeezed out from the tab when pressed down.

For Laminate Shingles place 4 spots of roof cement evenly spaced under each shingle about the size of a quarter then press firmly into place. Please be aware that excessive amounts of cement could blister the shingles. After the spots are placed, the tab must be pressed firmly onto the shingle beneath it to start the bond.

If the decision is made to make repairs as indicted above without damage to the shingles, Owens Corning's Limited Warranty on Roofing Shingles will be in full effect. Please keep in mind Owens Corning's Warranty covers manufacturing defects in the shingles only, we do not cover workmanship.

Should you have any additional questions, please contact the GETTECH Team at GETTECH@owenscorning.com.

Respectfully,

Alicia Zeiler

Alicia Zeiler
GETTECH Specialist
Owens Corning